

DISC SELECTION GUIDE





DISC SELEC



Operating Ratio

OSECO SAFETY CARTRIDGE™

95%

The Oseco Safety Cartridge is an innovative rupture disc solution designed to eliminate leaks, installation errors, and increase safety. Oseco's patented design allows three components of a traditional rupture disc system to be combined into one hermetically sealed component.

[[

90%



ELFAB OPTI-GARD

Reverse buckling high performance single disc solution across a wide range of sizes and burst pressures.

95%



ELFAB SAFE-GARD

Forward acting rupture disc that combines the versatility of conventional metal discs with the performance benefits of scored technology

90%



ELFAB OPTI-GARD SOLO

An innovative, low pressure rupture disc that works reliably even in demanding process conditions.

95%



OSECO FAS

Forward acting rupture disc with the lowest $\boldsymbol{K}_{\!_R}$ in the industry, designed for demanding rupture disc applications.

90%



ELFAB MILLI-GARD Designed for ultra-low burst pressure requirements. Can act as a single disc solution for either positive pressure or vacuum protection

60%



ELFAB UNIVERSAL ARMA-GARD A non-torque sensitive graphite rupture disc, Universal Arma-Gard has a holderless design for easy installation between industry standard flanges

85%



ELFAB FLO-TEL Flo-Tel is non-invasive to the process and is therefore unaffected by downstream pressure fluctuations or corrosion.

N/A

TION GUIDE

K _R Value	Size	Burst Pressure	Non- Fragmenting	Flow Direction	Service	Vacuum Support Required	Holder
0.78 K _{RGL}	1-12"	10-1160	Yes	+ (LGV	No	One Piece Unit
0.223 K _{RG} 0.19 K _{RL}	1-8"	80-2000	Yes	→	LGV	No	One Piece Unit
1.74 K _{RGL}	25mm-600mm 1-24"	0.35-70 (barg) 5-1015 (psig)	Yes		LGV	No	REV
0.68 K _{RL}	15mm-500mm 1/2-20"	3.1-185 (barg) 51-2680 (psig)	Yes	→	LGV	No	STD
0.8 K _{RGL}	25mm-150mm 1-6"	0.14-4.14 (barg) 2-60 (psig)	Yes		LGV	No	REV
0.223 K _{RG} 0.19K _{RL}	25mm-600mm 1–24″	2.07-344.7 (barg) 30-5000 (psig)	Yes		LGV	Yes	FRDI
N/A	50mm-300mm 2-12″	3-500 (mbarg) 0.044-7.25 (psig)	Yes		LGV	Yes	REV
0.69 K _{RGL}	25mm-350mm 1-14"	0.03-55 (barg) 0.44-798 (psig)	No	■	LGV	Yes	N/A
N/A	N/A	N/A	Yes	N/A	N/A	No	N/A

OUR PRODUCTS AND SERVICES PROVIDE

COMPLETE PEACE OF MIND



PRODUCT LINE



Oseco Safety Cartridge™

Single piece unit eliminates multiple leak paths



Ultra High Pressure Scored Reverse-Buckling Disc Assembly

Oseco HPSR: Single piece unit designed for a burst pressure over 6,000 psig



High Performance Reverse-Buckling Disc

Elfab Opti-Gard: Industry leading K_p value

Elfab Opti-Gard SoLo Innovative low pressure disc



High Performance Forward-Acting Scored Disc

Elfab Safe Gard: Low K_R value



Burst Detection Systems



Explosion Protection



Pressure Gauges

SERVICES

Engineering and Maintenance Training Seminars

Safety Surveys

Custom Engineered Solutions

Expedited Shipments

Emergency Response Team

OsecoElfab - UK office

Alder Road, North Shields Tyne and Wear, NE29 8SD UK Tel: +44 (0) 191 293 1234

OsecoElfab - US office

1701 W. Tacoma Broken Arrow, OK 74012 USA Tel: (918) 258-5626

Let us help you with all your pressure relief questions.

Contact Induchem at

Ireland: +353 (0)21 48 48 900 UK: +44 (0)1260 277234 sales@induchemgroup.com

www.induchemgroup.com